

PRODUCT DATA

RUST VETO[®] 377

RAISES WATER OFF WET METAL TO PREVENT RUST

Polar-type, water displacing **Rust Veto 377** actually raises water off wet metal to coat the entire metal surface with a long-lasting film. It slides under the most microscopic drops of water to spread a film of almost colorless rust preventive.

Metal doesn't need to be completely dry when **Rust Veto 377** is applied.

Rust Veto 377 can be used safely with many combinations of ferrous or nonferrous metals and alloys with no reaction.

TYPICAL PHYSICAL PROPERTIES

Humidity @ 100%	Withstands more than 30 days
Water Displacement Test	Meets Government specifications MIL-C-16173, Grade 3 and MIL-C-14201A, Grade 2
Film Thickness	0.0003" (0.3 mm)
Sprayability	Sprayable at 40°F
Flash Point	105°F
Cold Test	-5°F
Gravity	40.3° Baume
Pounds per Gallon	6.858 (0.82 kg/l)
Coverage	1,300 sq./ft. gallon



Houghton International Inc.

Madison and Van Buren Ave., P. O. Box 930, Valley Forge, PA 19482-0930

(610) 666-4000 Telefax (610) 666-1376

HOW TO USE

Apply by dip, spray or brush between 40° and 95°F. The film is easily removed by petroleum solvent or a medium duty cleaner such as Houghto-Clean 240, used at four to six ounces per gallon of water at 180-190°F.

WHERE TO USE

Rust Veto 377 is a real multi-purpose product. Use it across-the-board for indoor protection of critical surfaces or for packaged materials. Examples are hard water, anti-friction bearings, dies, tools, fixtures, gauges, polished steel, phosphatized surfaces (Houghto-Phos, Bonderized, Parkerized) and idle or stored machinery.

SHIPPING INFORMATION

This product is available in 55 U.S. gallon (208 liter) drums and in bulk.

SHIPPING CLASSIFICATION

Combustible Liquid, N.O.S. (Petroleum Lubricating Oil, N.O.S.)

STORAGE/HANDLING/DISPOSABILITY

No health or safety hazards exist when **Rust Veto 377** is stored, used and disposed of in accordance with instructions given on the Material Safety Data Sheet for this product.

WARRANTY

The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of Houghton products are not to be construed as recommending the infringement of any patent.

EXPORT STATEMENT

This commodity and its technology are subject to the export control laws and regulations of the United States Government. Buyer agrees that it shall not make any disposition, by way of export, diversion, transshipment, re-export or otherwise, except as expressly permitted under United States law.

4/01