

Rust Veto 4240

Solvent based rust preventive

DESCRIPTION

Rust Veto 4240 is a new solvent based rust preventive that rapidly displaces and separates water. The product exhibits a very thin, dry to touch film which, if applied properly, offers up to one year of indoor rust protection. Extremely low odor properties make this product very operator friendly.

FEATURES / BENEFITS

- Low odor
- Excellent humidity rust protection
- Exceptionally dry to touch film
- High flash - 195°F (90.56°C)
- Displaces water
- Fast water separation
- Easily removed
- For use with all metals
- Barium-free
- Low freeze and pour point
- Reduced drag-out
- Thin film protects your parts without excessive carry-off which reduces usage and cost.
- Low-odor nature of the products optimizes worker acceptance.
- Displaces water or process fluids from wet parts to rapidly begin the corrosion inhibition process.
- Separates any displaced water from itself to optimize both corrosion inhibition and bath life.
- The high flash point reduces the potential for flammability and may reduce fire insurance premiums.
- Rapid drying permits handling of parts shortly after application which expedites process flow and packaging.

DATA (TYPICAL VALUES)

Appearance	Clear amber
Non-Volatile	6%
Specific Gravity	0.79
Copper Corrosion ASTM D-130	1a
Viscosity @ 100°F SUS	26
Flash Point, PMCC	195°F
Film Thickness	0.036 mls
Film Type	Dry to touch film
Water Displacement	Passes
Water Separation	Passes
Humidity @ 120°F/100% RH	Passes 30+ days
Polished Panels	

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

Date | version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.