

Hocut 776-RHS

Low foaming, semi synthetic coolant

DESCRIPTION

Today's manufacturing environment requires products that are capable of performing in many applications. **Hocut 776-RHS** is a versatile, semi-synthetic coolant for machining and grinding of ferrous and nonferrous metals in medium duty operations. It is formulated with emulsifiers, lubricity additives and inhibitors that offer excellent residual fluid film corrosion protection .

CONCENTRATION CHECKS

The refractometer factor for **Hocut 776-RHS** is 1.7. Multiply the refractometer reading by this factor to obtain the product concentration.

RECOMMENDED CONCENTRATIONS

| | |
|-----------|--------------|
| Machining | 1:10 to 1:20 |
| Grinding | 1:20 to 1:25 |

DATA (TYPICAL VALUES)

| | |
|-------------------------|----------------------|
| Appearance, Neat | Clear amber fluid |
| Appearance, 5% Emulsion | Transparent dilution |
| pH, 5% Emulsion | 9.3 |
| Pounds per U.S. Gallon | 8.3 |

Date | version
Code

FEATURES/ BENEFITS

- Excellent corrosion protection for in process protection of machinery and parts
- Clean running and maximizes worker acceptance
- Waste treatable and assures low treatment costs
- Enhanced lubricity provides extended tool life and reduces tooling cost.
- Provides improved part finish which reduces overall cost through reduced rework and scrap rates
- Bio-stable formulation extends sump life indefinitely, reducing waste treatment and recharge costs.
- Allows grinding wheels to run clean with less loading which saves money by extending time between wheel dressing and wheel changes.
- Provides enhanced corrosion inhibition eliminating costly machine tool repair and scrap rate.
- Low oil content reduces costs by preventing wheel loading, which extends the time between required redressing of wheel, and by removing heat which increases tool and wheel life.

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.