

DASCOLUBE AW2

Spindle Oil

DESCRIPTION

Dascolube AW 2 spindle oil is made from the finest quality basestock, specifically selected to provide exceptional resistance to oxidation and degradation.

Dascolube AW 2 spindle oil incorporates special anti-wear additives and is designed to meet the requirements for major spindle OEMs in high speed or high pressure applications.

FEATURES / BENEFITS

- Excellent anti-wear protection
- Resistance to oxidation and rust
- Good water separation
- Excellent cooling properties
- Excellent filterability
- Resistance to sludge formation
- Hydrolytically stable
- Non-corrosive to steel and copper alloys
- Low pour point

DATA (TYPICAL VALUES)

	TEST METHOD	
Viscosity @40°C	ASTM D2161	2.4 cSt
Specific Gravity	ASTM D1298	0.805
Flash Point, COC	ASTM D92	120°C
Pour Point, °F	ASTM D97	-10
Color	ASTM D1500	1
Rust Test	ASTM D665A/B	Pass

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.

4/19/2012 / version
Code



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.