

# WALTER VALENITE VALCOOL® VP915

## Synthetic Metalworking Fluid

VP915 is a 100% tramp oil rejecting synthetic metalworking fluid. It is formulated to machine cast iron, steel, and stainless steel.

### KEY PRODUCT BENEFITS

- Rejects tramp oil
- 100% true synthetic
- Excellent corrosion protection
- Excellent tool life/wheel life
- Pleasant odor
- Cleaner working environment
- Low maintenance costs
- Low foaming

### LABORATORY INFORMATION

Appearance, Neat	Light Yellow
Appearance, 5% Dilution	Water White
Specific Gravity	1.055 +/- .02
Pounds per Gallon	8.776 lbs.
pH, 5% Dilution	9.3 +/- .02
Nitrites	None
Chromates	None
Mercury Compounds	None

#### WALTER NORTH AMERICA

Walter USA, LLC  
N22W23855 RidgeView Pkwy W  
Waukesha, WI 53188, USA  
800-945-5554  
service.us@walter-tools.com

[www.walter-tools.com/us](http://www.walter-tools.com/us)

Walter Canada  
N22W23855 RidgeView Pkwy W  
Waukesha, WI 53188, USA  
800-945-5554  
service.ca@walter-tools.com

[www.youtube.com/waltertools](http://www.youtube.com/waltertools)


Walter Tools S.A. de C.V.  
Boulevard Louis Donaldo Colosio 2255  
2do Piso, Colonia San Patricio  
25204 Saltillo, Coahuila, Mexico  
+52 (844) 450-3500  
service.mx@walter-tools.com

[www.facebook.com/waltertools](http://www.facebook.com/waltertools)



## \_ MONITORING CONCENTRATION

### Refractive Index Concentration



In order to maintain a bacteria free environment, thoroughly clean all areas of the coolant system before charging it with new coolant.

#### INSTRUCTIONS FOR USE

1. Determine the system size in gallons
2. Multiply the total system size by the recommended % of VP915
3. Slowly add the recommended amount of VP915 to the water and mix well
4. Always add VP915 to water, never in reverse order

#### Available Quantities:

5 gallon pails, 55 gallon drums, 220 gallon disposable totes, 275 gallon bins, bulk tanker

For more safety information visit: [www.osha.gov/SLTC/metalworkingfluids/metalworkingfluids\\_manual.html](http://www.osha.gov/SLTC/metalworkingfluids/metalworkingfluids_manual.html)

**DISCLAIMER:** The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date issued. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use are out of our control, Walter USA, LLC. makes no warranty regarding the accuracy of such data or its suitability for any purchaser's use or for any consequence of its use. The data in this product information sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product. Walter Valenite assumes no responsibility for injury to the recipient or to third persons or for any damage to any property and the recipient assumes all such risks.